

Material

Body: DI
 Filter Screen: SS
 Total area of mesh: 3-4DN


Main Technical Parameters

Working pressure: 10 bar, 16bar
 Shell pressure: 15bar, 24bar
 Seated pressure: 11bar, 17.6bar

DIMENSION			
DN	END FLANGE PN10/16		
	L	H	H1
40	200	115	168
50	220	155	195
65	290	198	270
70	310	210	295
100	350	250	344
125	400	305	422
150	480	358	485
200	550	450	602
250	660	503	710
300	720	578	815



100X Solenoid Distance Control Ball Float Valve



Material

Body, Bonnet: DI
 Disc: CARBON STEEL
 BALL: SS
 Sealing gasket: NBR
 Diaphragm: Reinforced
 nylon rubber
 Spring: SS

Main Technical Parameters

Working pressure: 10 bar
 Shell pressure: 15bar
 Seated pressure: 11bar

DN	DIMENSION			
	OUTLINE mm	END FLANGE PN10-16		
	L	D	D1	n-d1
50	203	165	125	4-φ18
65	215	185	145	4-φ18
80	241	200	160	8-φ18
100	260	220	180	8-φ18
125	300	250	210	8-φ18
150	330	285	240	8-φ22
200	400	340	295	8-φ22 12-φ22
250	480	395 405	350 355	12-φ22 12-φ26
300	550	445 460	400 410	12-φ22 12-φ26
350	622	505 520	460 470	16-φ22 16-φ26
400	685	565 580	515 525	16-φ26 16-φ30